



6040 DTF HEAT PRESS MACHINE

UP-SLIDING PNEUMATIC DOUBLE-STATION HEAT PRESS MACHINE
WITH INFRARED POSITIONING FOR T-SHIRT TEFLON HEATING PLATE)
双工位上滑式红外线定位气动烫画机(特氟龙发热板)

- 1.Optional to install one side(cross)infrared positioning device.pressing point is more accurate.
可选单边一只(十字)红外线定位压烫定位点更精准.
- 2.Optional toinstall two side (double cross) infrared positioning device,pressing ranges more accurate
可选配单边两只(井)红外线定位压烫，定位范围更精准.
- 3.Infrared is a multi-joint magnet that can be moved or adjusted arbitrarily.
多关节吸盘式红外线，可任意移动或多向调节.



可选配/Optional: Clothes holding device 衣物收夹料装置.

可选配:发热板左右自动移位
Optional: heating plate moves left and right automatically.

FEATURES

- 1.The machine body is thickened, and the whole base is bent and welded to make the bearing force stronger and more stable.
- 2.Up heating plate moves left and right by hand, which can bemoved according to the speed of the operator.
- 3.Move left and right to the leftmost or rightmost automatic induction heating down, or manually press down.
- 4.Lower plate hanging U-shaped design,can be inset T-Shirt and heating press,the bottom plate mold can be easily replaced.
- 5.Industrial grade 3cm thickness heating plate and 12 group heating pipe casting integration, strong thermal conductivity, small amount of variation, safe, durable and uniform heating.
- 6.Time, temperature, counting integrated control panel display, simple and convenient to operate, good stability.
- 7.The machine adopts air pressure mode, between the upper heating plate and the cylinder with thousands of steel springs automatically find the heating plate and the lower plate completely balance.
- 8.The lifting speed of the heating plate is adjustable, and the cylinder pressure range is 0-10 bar.

产品特点

- 1.加厚机身底座整体折弯焊接，使得承压能力更大，更牢固、更稳定。
- 2.上发热板上滑动,手推式左右移动,可根据服作业人员熟练度随心移动。
- 3.左右平衡移动至最左边或者最右边,自动感应下压或手动按键下压。
- 4.下底板悬空U型设计,可套成衣单层压烫，在板模具可随意简单更换。
- 5.工业级3cm厚度发热板与12组发热管浇筑一体，导热性强，变形量小，安全耐用。发热均匀。
- 6.时间、温度、计数一体控制面板显示，按键调节简单方便,稳定性好。
- 7.采用气压方式，上发热板与气缸之间用四颗精钢弹簧自动找发热板与下底板平衡。
- 8.加热板升降速度可调，气缸压力范围0-10公斤。

Heating plate size 加热板尺寸(cm/inch)	Voltage 电压(V)	Power 功率(kw)	Temperature range 温度范围(°C)	Time range 时间范围(s)	Weight 重量(kg)	Packing size 包装尺寸(cm)
40x30 / 16x12	220/110	1.3/1	0-299	0-999	80	93x68x73
40x40 / 16x16	220/110	2/1.5	0-299	0-999	90	93x68x73
50x40 / 20x16	220/110	2.5/1.8	0-299	0-999	120	108x85x80
60x40 / 24x16	220/110	3/2	0-299	0-999	140	108x85x80
70x50 / 28x20	220/110	5/3.5	0-299	0-999	180	165x85x80